

| Accessories | |
|-----------------------------|---|
| Supplied Accessories | Remote control, AAA batteries x 4, power cord (4.5m) x 1, computer cable, cable cover, adapter cover, user's manuals and CD, application CD and DVD, USB cable, interactive pen x 2, pen tips x 4, AA batteries x 2, PIN code sticker |
| Optional Accessories | Finger touch unit (FT-01B), interactive pen (I-PEN4), wireless adapter (USBWL5G), wall mount (HAS-WM05), table stand kit (TT-03), Apple TV bracket (HAS-RB01) |
| Replacement Parts | |
| Lamp | DT01411 with filter |
| Remote Control | HL03033 |
| Filter | UX37191 |

Projection Throw Chart (In inches)

| Screen Size 16:10 | Throw Distance | |
|-------------------|---|--------------------------------------|
| Diagonal | Distance from edge of projector to screen | Distance from mirror cover to screen |
| 60 | 5.0 | 16.1 |
| 70 | 7.8 | 18.9 |
| 80 | 10.5 | 21.6 |
| 90 | 13.3 | 24.4 |
| 100 | 16.1 | 27.1 |

Throw Ratio: (distance : width)
0.2 : 1 from edge of projector
0.3 : 1 from mirror cover



- Comes bundled with Maxell interactive projectors
- World-class integrated software
- Collaborate, integrate, annotate



MX0656-Rev.1-03/19
All specifications subject to change without notice.
3LCD and the 3LCD logo are registered trademarks of the Seiko Epson Corporation.
©2019 Maxell Corporation of America. All Rights Reserved.

| Specifications | | |
|-------------------------------|--|---|
| Display | Projection Technology | 3LCD, 3 chip technology |
| | Resolution | WXGA 1280 x 800 |
| | White Light Output | 3,700 ANSI lumens |
| | Color Light Output | 3,700 ANSI lumens |
| | Colors | 16.7 million colors |
| | Aspect Ratio | Native 16:10, 4:3, 16:9, 14:9 and zoom compatible |
| | Contrast Ratio | 20,000 : 1 (using active IRIS) |
| Lens & Operation | Throw Ratio (distance : width) | 0.2 : 1 from edge of projector to screen 0.3 : 1 from mirror cover to screen |
| | Focus Distance | 16" - 27" from mirror cover to screen |
| | Display Size | 60" - 100" |
| | Lens | f = 4.21 mm, digital zoom x 1.35, powered focus |
| | Lamp Wattage | 250W |
| | Expected Lamp Life* | Approximately 4,000 hours (standard mode) 6,000 hours (Eco-2 mode) |
| | Expected Filter Life** | Approximately 4,000 hours |
| Compatibility | Speaker Output | 16W x 1 |
| | Keystone | H and V: +/- 5° |
| | Computer | VGA, SVGA, WXGA, WXGA+, SXGA, SXGA+, UXGA (compressed), MAC 16" |
| | H-Sync | 15 kHz - 106 kHz |
| | V-Sync | 50 Hz - 120 Hz |
| | Composite Video | NTSC, NTSC4.43, PAL, PAL-M, -N, SECAM |
| | Component Video | 480i, 480p, 576i, 576p, 1080i, 1080p |
| Connectors | HDMI | 480i, 480p, 576i, 576p, 1080i, 1080p, computer signal TMDS clock 27 MHz - 150 MHz |
| | MHL In | HDMI connector x 1 (HDCP compliant) shared with HDMI 1 input |
| | Digital Input | HDMI x 2 (HDCP compliant) (1 shared with MHL) |
| | HDMI In | HDMI Connector x 2 (HDCP compliant) |
| | Computer Input 1 | 15-pin mini D-sub x 1 (shared with analog component video input) |
| | Computer Input 2 | 15-pin mini D-sub x 1 (shared with component video input and monitor out) |
| | Computer Monitor Output | 15-pin mini D-sub x 1 (shared with computer in 2) |
| Ratings & Warranty | Video Input | |
| | Composite Video | RCA jack x 1 |
| | Component Video | 15-pin D-sub x 2 (shared with computer in 1/2) |
| | Audio Input | 3.5 mm stereo mini jack x 1, RCA jack (L/R) x 1 |
| | Audio Output | 3.5 mm stereo mini jack x 1 |
| | Network LAN Wired | RJ-45 port (10 base-T / 100 base-TX) |
| | Network LAN Wireless | USB-A, IEEE802.11 b/g/n - optional wireless adapter required |
| USB | Type A x 2 (PC-less presentation, wireless adapter) Type B x 1 (USB display or mouse control) | |
| Microphone In | 3.5 mm mini jack x 1 | |
| Control Terminals | 9-pin D-sub x 1 (RS-232 control) | |
| Power Supply | AC100-120V / AC220-240V, 50/60Hz | |
| Power Consumption | 380W/360W | |
| Operating Temperature | 32°F - 104°F (0°C - 40°C) | |
| Dimensions (W x D x H) | 14.8" x 14.2" x 5.4" (excluding protruding parts) | |
| Weight | Approximately 10.1 lbs | |
| Approvals | UL 60950-1 / cUL, FCC part 15 subpart B Class B | |
| Warranty | 3-year limited parts and labor Extended Service Contract available (additional cost) | |

* Actual lamp life will vary by individual lamp based on environmental conditions, selected operating mode, user settings and usage. Hours of average lamp life specified are not guaranteed and do not constitute part of the product or lamp warranty. Lamp brightness decreases over time.

** Actual filter life will vary by individual filter based on environmental conditions, selected operating mode, user settings and usage. Hours of average filter life specified are not guaranteed and do not constitute part of the product warranty.

