MC-WU5501 LCD Projector



Accessories and Lenses		
Supplied Accessories	Remote control, power cord, computer cable, AA batteries x2, lens cover, security label, user's manual CD, user's manual, application CD	
Optional Accessories	Wireless adapter (USBWL11N)	
Replacement Parts		
Lamp	DT01931M	
Remote Control	HL03037	
Filter	UX41161	

Projection Throw Chart (In inches)

Screen Size 16:10		Throw Distance	
Diagonal	Width	Min	Max
30	25	33	58
60	51	68	118
80	68	91	158
100	85	115	198
200	170	231	397
300	254	348	597

Throw Ratio: 1.4 - 2.3:1 (distance: width)







MX0660-Rev.1-11/19
All specifications subject to change without notice.
3LOD and the 3LCD logo are registered trademarks of the Seiko Epson Corporation. Crestron®,
Crestron®, Crestron e-Contro®, e-Contro®, Crestron Connected®, Fusion RV®, Crestron RoomView®
and RoomWiew™ are trademarks or registered trademarks of Crestron Electronics, Inc. in the United
States and other countries. HDMI, the HDMI Logo, and High-Definition Multimedia Interface are
trademarks or registered trademarks of HDMI Licensing ILLC in the United States and other countries.
HDBaseT™ and the HDBaseT Alliance logo are trademarks of the HDBaseT Alliance. iPad and iPhone
are registered trademarks of Apple Inc., registered in the U.S. and other countries. All other brand or
product names are trademarks or registered trademarks of their respective holders.

©2019 Maxell Corporation of America. All Rights Reserved.

Spec	Specifications			
. Ar	Projection Technology	3LCD, 3 chip technology		
	Resolution	WUXGA 1920 x 1200		
	White Light Output	5,200 ANSI lumens		
	Color Light Output	5,200 ANSI lumens		
	Colors	16.7 million colors		
g	Aspect Ratio	Native 16:10 / 4:3, 14:9 and 16:9 compatible		
Dis	Contrast Ratio	10,000 : 1 (using active IRIS)		
	Throw Ratio (distance : width)	1.4 - 2.3 : 1		
	Focus Distance	33" - 597"		
	Display Size	30" - 300"		
_	Lens	f = 19.8 - 33.9, x 1.7 manual zoom, focus & lens shift		
atio	Lamp Wattage	300W		
Lens & Operation	Expected Lamp Life*	Approximately 4,000 hours (standard mode) 6,000 hours (Eco mode)		
	Expected Filter Life**	Approximately 10,000 hours		
	Speaker Output	16W		
	Keystone	H and V: +/- 30°		
Compatibility	Computer	VGA, SVGA, XGA, WXGA, WXGA+/SXGA/SXGA+/WSXGA+/ UXGA/WUXGA, MAC 16"		
	H-Sync	15 kHz - 106 kHz		
	V-Sync	50 Hz - 120 Hz		
	Composite Video	NTSC, NTSC4.43, PAL, PAL-M, -N, SECAM		
	Component Video	480i, 480p, 576i, 720p, 1080i, 1080p		
	HDMI	480i, 480p, 576i, 720p, 1080i, 1080p, Computer signal TMDS clock 27 MHz - 150 MHz		
	Digital Input	HDMI x 2		
	HDMI Output	HDMI x 1		
	Computer Input	15-pin mini D-sub x 1		
	Computer Monitor Output	15-pin mini D-sub x 1, HDMl x 1		
	Video Input			
ပ္	S-Video	N/A		
ctc	Composite Video	RCA jack x 1		
i e	Component Video	15-pin mini D-sub x 1 (shared with computer Input)		
Connectors	Audio Input	3.5 mm stereo mini jack x 1, RCA jack (L/R) x 1		
	Audio Output	3.5 mm stereo mini jack x 1		
	Network LAN Wired	RJ-45 port (10 base-T / 100 base-TX)		
	Network LAN Wireless	USB-A, IEEE802.11 b/g/n - optional wireless adapter required		
	HDBaseT	N/A		
	USB	Type A x 1 (wireless network)		
	Control Terminals	9-pin D-sub x 1 (RS-232 control)		
Ratings & Warranty	Power Supply	AC 100-120V/220-240V, 50/60Hz		
	Power Consumption	440W / 420W		
	Operating Temperature	32°F - 95°F (0°C-35°C) (Standard) 32°F - 104°F (0°C-40°C) (Eco Mode)		
	Dimensions (W x D x H)	18.1" x 13.1" x 5.4" (excluding protruding parts)		
	Weight	Approximately 14 lbs.		
aţi	Approvals	UL 60950-1 / cUL FCC Part 15 subpart B class A		
ığ.	Warranty	3-year limited parts and labor		

- Actual lamp life will vary by individual lamp and based on environmental conditions, selected operating mode, user settings and usage. Hours of average lamp life specified are not guaranteed and do not constitute part of the product or lamp warranty. Lamp brightness decreases over time.
- ** Actual filter life will vary by individual filter and based on environmental conditions, selected operating mode, user settings and usage. Hours of average filter life specified are not guaranteed and do not constitute part of the product warranty.













Toll Free: 1.800.377.5887 Web: www.maxellproav.com



Extended Service Contract available (additional cost)





