

## Accessories and Lenses

<b>Supplied Accessories</b>	Remote control, power cord, computer cable, AA batteries x 2, adapter cover, terminal cover, manual CD, user's manual, application CD, security label, HDMI bracket x 2, binder x 2
<b>Optional Accessories</b>	Wireless adapter (USBWL11N)
<b>Optional Lenses</b>	7 optional lenses are available, FL710M, USL701, FL701, SL712, ML713, LL704, UL705 (This model ships without a lens)
<b>Replacement Parts</b>	
<b>Lamp</b>	DT01881M
<b>Remote Control</b>	HL02805
<b>Filter</b>	UX40821

## Projection Throw Chart

Screen Size	16:10		Throw Distance	
	Diagonal	Width	Min	Max
30	25	45	75	
80	68	117	198	
100	85	146	248	
150	127	219	371	
200	170	291	494	
250	212	363	617	
300	254	435	740	
600	509	869	1478	

Throw Ratio: 1.7 - 2.9 : 1 (distance : width)  
Screen size and throw distance are measured in inches with standard lens ML713.

## Projection Lens Chart

Lens	Inches	Meters
<b>FL710M</b>	4.27	0.11
<b>USL701</b>	67 - 87	1.71 - 2.21
<b>FL701</b>	69	1.76
<b>SL712</b>	100 - 151	2.54 - 3.83
<b>ML713</b>	146 - 248	3.71 - 6.29
<b>LL704</b>	240 - 407	6.09 - 10.34
<b>UL705</b>	407 - 691	10.34 - 17.56

Projection distances measured in inches and meters with standard lens and optional lenses when projecting onto a 100" diagonal screen.



MX0672-Rev.2-11/19

All specifications subject to change without notice.

3LCD and the 3LCD logo are registered trademarks of the Seiko Epson Corporation. Crestron®, Crestron e-Control®, e-Control®, Crestron Connected®, Fusion RV®, Crestron RoomView® and RoomView™ are trademarks or registered trademarks of Crestron Electronics, Inc. in the United States and other countries. HDMI, the HDMI Logo, and High-Definition Multimedia Interface are trademarks or registered trademarks of HDMI Licensing LLC in the United States and other countries. HDBaseT™ and the HDBaseT Alliance logo are trademarks of the HDBaseT Alliance. All other brand or product names are trademarks or registered trademarks of their respective holders. ©2019 Maxell Corporation of America. All Rights Reserved.

## Specifications

Display	<b>Projection Technology</b>	3LCD, 3 chip technology
	<b>Resolution</b>	WUXGA - 1920 x 1200
	<b>White Light Output</b>	7,000 ANSI lumens
	<b>Color Light Output</b>	7,000 ANSI lumens
	<b>Colors</b>	16.7 million colors
	<b>Aspect Ratio</b>	Native 16:10 and 4:3 / 16:9 compatible
	<b>Contrast Ratio</b>	10,000 : 1 (using active IRIS)
Lens & Operation	<b>Throw Ratio (distance : width)</b>	Specifications will vary depending on which lens is used with the projector
	<b>Focus Distance</b>	43.3" - 1480.3"
	<b>Display Size</b>	30" - 600"
	<b>Lens</b>	Specifications will vary depending on which lens is used with the projector (This model ships without a lens)
	<b>Lamp Wattage</b>	430W
	<b>Expected Lamp Life*</b>	Approximately 2,000 hours (standard mode), 4,000 hours (Eco mode), 1,000 hours (portrait mode)
	<b>Expected Filter Life**</b>	Approximately 20,000 hours
Compatibility	<b>Speaker Output</b>	16W (8W x 2 stereo)
	<b>Keystone</b>	H and V: +/- 5° (with standard lens)
	<b>Computer</b>	VGA, SVGA, XGA, WXGA, WXGA+/SXGA/SXGA+/WSXGA+/UXGA/WUXGA, MAC 16"
	<b>H-Sync</b>	15 kHz - 106 kHz
	<b>V-Sync</b>	50 Hz - 120 Hz
	<b>Composite Video</b>	NTSC, NTSC4.43, PAL, PAL-M, -N, SECAM
	<b>Component Video</b>	480i, 480p, 576i, 720p, 1080i, 1080p
Connectors	<b>HDMI</b>	480i, 480p, 576i, 720p, 1080i, 1080p, Computer signal TMDS clock 27 MHz - 150 MHz
	<b>Digital Input</b>	HDMI x 2, HDBaseT x 1, Display Port x 1, SDI x 1
	<b>Computer Input</b>	15-pin mini D-sub x 1
	<b>Computer Monitor Output</b>	15-pin mini D-sub x 1
	<b>Video Input</b>	
	S-Video	N/A
	Composite Video	RCA jack x 1
Component Video	15-pin mini D-sub (shared with computer input)	
<b>Audio Input</b>	3.5 mm stereo mini jack x 1, RCA x 1	
<b>Audio Output</b>	3.5 mm stereo mini jack x 1	
<b>Network LAN Wired</b>	RJ-45 jack x 1	
<b>Network LAN Wireless</b>	USB-A, IEEE802.11 b/g/n - optional wireless adapter required	
<b>HDBaseT</b>	RJ-45 jack x 1	
<b>USB</b>	Type A x 1 (wireless network)	
<b>Wired Remote Control</b>	3.5 mm stereo mini jack (IN/OUT)	
<b>Control Terminals</b>	9-pin D-sub x 1 (RS-232 control)	
Ratings & Warranty	<b>Power Supply</b>	AC90-132V / AC198-264V, 50/60Hz
	<b>Power Consumption</b>	580W / 560W
	<b>Operating Temperature</b>	32°F - 113°F (0°C - 45°C)
	<b>Dimensions (W x D x H)</b>	19.6" x 16.8" x 6.1" (without lens)
	<b>Weight</b>	Approximately 24.5 lbs
	<b>Approvals</b>	UL 60950-1 / cUL FCC Part 15 subpart B class A
	<b>Warranty</b>	3-year limited parts and labor Extended Service Contract available (additional cost)

\* Actual lamp life will vary by individual lamp based on environmental conditions, selected operating mode, user settings and usage. Hours of average lamp life specified are not guaranteed and do not constitute part of the product or lamp warranty. Lamp brightness decreases over time.

\*\* Actual filter life will vary by individual filter based on environmental conditions, selected operating mode, user settings and usage. Hours of average filter life specified are not guaranteed and do not constitute part of the product warranty.

