

Accessories and Lenses

Supplied Accessories	Power cable, RGB cable, remote control, AA batteries x 2, user's manual (concise)
Optional Accessories	USBWL5G wireless adapter
Optional Lenses	NA
Replacement Parts	
Remote Control	HL03037
Filter	UX44211

Projection Throw Chart

Screen Size 16:10		Throw Distance	
Diagonal	Width	Min	Max
30	25	31	45
60	51	65	92
80	68	87	123
100	85	109	154
200	170	221	311
300	254	333	468

Throw Ratio: 1.3 - 1.8 : 1 (distance : width)
Screen size and throw distance are measured in inches.

Specifications

Display	Projection Technology	3LCD, 3 chip technology
	Resolution	WXGA - 1280 x 800
	White Light Output	3,500 ANSI lumens
	Colors	1.07 billion colors
	Aspect Ratio	Native 16:10, 4:3, 16:9, 14:9 and zoom compatible
	Contrast Ratio	2,000,000 : 1
Lens & Operation	Throw Ratio (distance : width)	1.3 - 1.8 : 1
	Focus Distance	32" - 468"
	Display Size	30" - 300"
	Lens	x 1.4 manual zoom and focus
	Lens Offset	43%
	Expected Light Source Life*	20,000 hours (Normal and Whisper), 30,000 hours (Long life 1), 40,000 hours (Long life 2)
Compatibility	Expected Filter Life**	Approximately 5,000 hours
	Speaker Output	16W
	Keystone	Auto V, Manual H/V (±30°)
	Computer	VGA, SVGA, XGA, WXGA, WXGA+, SXGA, WSXGA+, UXGA (compressed), MAC16"
	H-Sync	15 kHz - 106 kHz
	V-Sync	50 Hz - 120 Hz
Connectors	Composite Video	RCA jack x 1
	Component Video	15-pin mini D-sub x 2 (shared with computer in 1, in 2/monitor out)
	Audio Input	3.5 mm stereo mini jack x 1, RCA jack (L/R) x 1
	Audio Output	3.5 mm stereo mini jack x 1
	Network LAN Wired	RJ-45 port (10 base-T/100 base-TX)
	Network LAN Wireless	USB-A, IEEE802.11 a/b/g/n/ac - optional wireless adapter required
Ratings	USB	Type A x 1 (PC less presentation, wireless adapter or 5V/2A power supply) Type B x 1 (USB mouse control)
	Control Terminals	9-pin D-sub x 1 (RS-232 control)
	Power Supply	AC100-120V / AC220-240V, 50/60Hz
	Power Consumption	240W / 230W
	Operating Temperature	32°F - 104°F (0°C - 40°C) Normal mode 95°F - 104°F / 35°C - 40°C brightness is reduced automatically)
	Dimensions (W x D x H)	13.0" x 10.6" x 2.7" (excluding protrusions)
	Weight	Approximately 7.9 lbs.
	Approvals	UL 60950-1 / cUL FCC Part 15 subpart B class B

* Actual light source life will vary by individual light source based on environmental conditions, selected operating mode, user settings and usage. Hours of average light source life specified are not guaranteed and do not constitute part of the product or light source warranty. Light source brightness decreases over time.

** Actual filter life will vary by individual filter based on environmental conditions, selected operating mode, user settings and usage. Hours of expected filter life specified are not guaranteed and do not constitute part of the product warranty.



MX0716-Rev.2-01/21

All specifications subject to change without notice.
3LCD and the 3LCD logo are registered trademarks of the Seiko Epson Corporation.
Crestron®, Crestron®, Crestron e-Control®, e-Control®, Crestron Connected®, Fusion RV®, Crestron RoomView® and RoomView™ are trademarks or registered trademarks of Crestron Electronics, Inc. in the United States and other countries. HDMI, the HDMI Logo, and High-Definition Multimedia Interface are trademarks or registered trademarks of HDMI Licensing LLC in the United States and other countries. All other brand or product names are trademarks or registered trademarks of their respective holders.
©2021 Maxell Corporation of America. All Rights Reserved.



HDMI

Maxell Corporation of America

Toll Free: 1.800.377.5887

Web: www.maxellproav.com

